rk MILES 2023 ROOFING PRODUCT QUICK COMPARE

PRODUCT	LOCATION	NOTES
Felt Underlayment 15LB - 15F 30LB - 30F	ALL LOCATIONS	 Affordable underlayment option. 5lb roll = 432 sq. ft. 30lb roll = 216 sq. ft. No price difference between weights.
RhinoRoof Synthetic RHINO20	MD	 15lb synthetic felt underlayment. Easy to use in cold weather. Longer lasting than traditional felt.
RhinoRoof Granulated RHINOG	MD	 Granulated, waterproof barrier. Self-adhesive. Applied directly to sheathing.
Starwrap DBSP	M, MD, W, H	 100% recyclable, synthetic underlayment. 7 mils thick - 10 sq. per roll. 5x lighter, 25x stronger than felt.
Tri-flex XT TRIFLEX	M, MD, MO, W, H, S B, MT, SJ, WT	 Synthetic roofing underlayment. 20x stronger than 30lb felt - 7 mils thick. Coated with slip-resistant polymers.
Top Guard II TG	M, MD, W, H, MO, S B, SJ, WT	 Synthetic roofing underlayment. Five layer construction -100% waterprtoof. 5'x 200' - 10 sq. per roll.
Grace Ice and Water 2sq. WRG	ALL LOCATIONS	 Self-adhesive underlayment. Self-sealing around nail holes etc. 40 mils thick.
1sq. WRG1	M, W, MO, S, B, MT, SJ, WT	
Grace Select Ice & Water WRGSEL	M, W	 Self-adhesive underlayment 2 sq. roll size. Light weight, easy install. 25 mils thick.
Grace Hi-Temp Ice & Water WRIGHT	M, MD, MO, S, B, SJ, WT	 Self-adhesive underlayment. Up to 120 days UV exposure. 40 mils thick.
IKO Armourgard IWS	ALL LOCATIONS	 Economical, self-adhesive underlayment. 2 sq. per roll (3'x65') - 70 mils thick. Granulated finish for slip resistance.
IKO Stormshield ISS	W, H	 Economical, self-adhesive underlayment. 2 sq. per roll (3'x65') - 40 mils thick. Tear-resistant membrane.
IKO Stormtite IST	MO, B, MT, SJ	 Affordable, synthetic alternative to felt. 10 sq. per roll (4'x250'). Light weight and flexible - easy to install.

Location Key

M - Manchester MD - Middlebury W - Williamstown H - West Hatfield MO - Morrisville S - Stowe B - Barre MT - Montpelier SJ - Saint Johsnbury WT - Waitsfield

*Consult with an rk MILES salesperson for further information and pricing *Detailed individual spec sheets available upon request

