HydroGap[®] SA, is the first ever self-adhered WRB with a 1mm drainage space. By integrating a continuous drainage space with a continuous acrylic adhesive, HydroGap[®] SA creates an unmatched air and moisture barrier in the wall assembly. The

ADHERED

E

DRAIN

HOL

SEWRAP

with a continuous acrylic adhesive, HydroGap[®] SA creates an unmatched air and moisture barrier in the wall assembly. The 1mm spacer provides an ideal gap behind any exterior foam, keeping any damaging effects out of the wall.

HydroGap[®] SA is the keystone of our high performance air barrier drainage assembly. When integrating HydroGap[®] SA into the details of a structure, it's important to use high performance flashing, like HydroFlash[®], to provide a consistently performing and durable wall system. In addition to the drainage capability, the vapor permeability of this system ensures protection from moisture as it allows condensation to escape to the exterior.



WIDTH 4.75 ft (1.45 m)

LENGTH PER ROLL 80 ft (24.38 m)

> MAX. UV EXPOSURE 120 days

COMPOSITION Polypropylene tri-laminate

> VAPOR PERMEABILITY 12 perms

ADHESION Continuous Acrylic

> FIRE RATING Class A

100% continuous acrylic adhesive technology provides true sealing around every fastener and penetration point

1mm spacers create a true drainage space with 96% drainage efficiency and removes water 2x faster than flat housewraps

Full line of flashing accessories available to complete the system and achieve warranty coverage for 20 years

Adheres to OSB, CDX, plywood, and CMU without the use of a primer above 25° F



